

## STANDARD FEATURES:

---

<b>Length</b>	53'
<b>Overall Width</b>	8 1/2'
<b>Deck Height</b>	Approx 59" at Front and 55 1/2" at Back
<b>Distributed Load</b>	Approx 75000 Lbs 10' Concentrated Load - Approx 60000 Lbs 4' Concentrated Load - Approx 50000 Lbs
<b>Tare Weight</b>	Approx 13700 Lbs
<b>GVWR</b>	37500 kg
<b>Landing Gear</b>	Jost Magnum 2 Speed Landing Gear
<b>King Pin</b>	Set at 24" - 1/4" or 3/8" Coupler Plate Available
<b>Main Beams</b>	Web: 3/16" High Tensile Flange: 3/8" x 6" High Tensile Steel
<b>Cross Members</b>	4" High Tensile Jr I Beam on 16" Centers
<b>Side Rail</b>	Tubing with 3/8 x 2" Tie Bar on Bottom of Jr I-Beam or 6" Channel with 3/8" x 2" Rub Rail Optional: 6" Channel with 3/8" x 3" HD Rub Rail Stake Pockets Set at 48" Centers Optional: Stake Pockets Set at 24" Centers
<b>Rear Bumper</b>	10 Gauge Plate Rear Bumper Rear Impact Guard Doepker ICC Panel at Back Optional: Dock Bumpers at Back of Trailer Optional: Single Point or Dual Tow Hooks at Back of Trailer
<b>Winches</b>	D/S or Staggered Design - 26 Winches with J-Hooks on Opposite Side Optional: Tarp Hooks on 24" Centers
<b>Decking</b>	2" x 6" T & G Fir Decking Optional: Hardwood Decking Optional: Coil Option - 2" x 6" T & G Fir Outside Main Rails, Hardwood Inside Main Rails
<b>Air System</b>	Aluminum Air Tanks Inline Air Filtration System Built into Glad hands Air Gauge Box with Window
<b>Tires</b>	Michelin or BF Goodrich
<b>Rims</b>	22.5 or 24.5: Various Steel and Aluminum Options
<b>Serial Plate(s)</b>	Canada/U.S.
<b>Safety Certified</b>	Yes

## SUSPENSION:

---

<b>System</b>	Hendrickson Intraax HXL5 Long Life Dressed Axle - AAT-23K-LDA-14 Air Ride with Cam Tube Enclosures 4' Sliding Suspension on 6" Spacings Optional: Doepker Auto Lift Management System with Meritor Control Valve Optional: Truckweight Wireless Scale System Optional: Chain Axle Slings on all Axles
<b>Brakes</b>	Abex 16 1/2" x 7" Extended Life
<b>Antilock Braking System</b>	Meritor Wabco 2S2M Optional: 4S2M or 6S4M (with 2 Indicator Lights)

<b>Axle Spread</b>	60" Tridem; 77-1/2" Track Width
<b>Auto Slack Adjusters</b>	Gunite
<b>Spring Brake Pots</b>	30/30 TSE Omnibrake Optional: TSE Ultra-Life
<b>Wheel End</b>	Cast Hub and Drum Optional: Duralight Hub and Centrifuse Drum Combinations Optional: Hubodometer - Metric or Imperial

## PAINT AND FINISH:

---

<b>Blast Preparation</b>	Completely Steel Shot Blasted
<b>Special Coatings</b>	Pure Zinc on Complete Outside Top To Bottom
<b>Primer</b>	PPG Epoxy Primer Inside and Out
<b>Top Coat</b>	PPG Urethane / Acrycote Systems - All Colours Available
<b>Professional Cure System</b>	Entire Trailer put in Heat Ovens for Optimal Paint Adhesion
<b>Safety</b>	Reflective Tape

## LIGHTING:

---

<b>Wiring Harness</b>	Severe Duty Sealed Harness System Custom Designed by Trucklite for our Light Packages
<b>Lighting</b>	Trucklite LED as per CMVSS with Side Signals Optional: 7 Wire Socket at Front or Back Optional: 4 Wire Socket at Front or Back Optional: Wide Load Lights

## PROTECTIVE:

---

<b>Mudflaps</b>	Doepker Mudflaps at Back of Trailer Optional: Mudflaps in Front of Brake Pots on Front Axle Optional: Mudflaps Full Width in Front of Landing Gear
<b>Toolbox &amp; Dunnage Options</b>	Optional: Set of Toolbox Brackets on D/S & C/S for a 43" or 55" Long Box Optional: 24" D x 24" H x 55" L Aluminum Checkerplate Toolbox Optional: 24" D x 24" H x 55" L Premium Smooth Aluminum Toolbox Optional: 24" D x 30" H x 55" L Premium Smooth Aluminum Toolbox Optional: 24" D x 24" H x 43" L Aluminum Checkerplate Toolbox Optional: 24" D x 24" H x 43" L Premium Smooth Aluminum Toolbox Optional: 24" D x 30" H x 43" L Premium Smooth Aluminum Toolbox Optional: Various Crossframe and Side Dunnage Options Available
<b>Spare Tire Carrier</b>	Optional: Spare Tire Carrier on C/S