

STANDARD FEATURES:

Length	20' 8" - Overall 193" - Center of Pintle to Center of 5th Wheel
Tare Weight	TBD
GVWR	18000 Kg
Frame	Web: Mild Steel Flange: High Tensile Steel
Hitch	Solid Hitch Design - 23" Height Safety Cable: 1/2" GR 70 Chain c/w 5 Ton Slip Hooks
Air System	Aluminum Air Tanks Inline Air Filtration System Built into Glad hands
Tires	Michelin or BF Goodrich
Rims	22.5 or 24.5: Various Steel and Aluminum Options
Serial Plate(s)	Canada / U.S
Safety Certified	Yes

SUSPENSION:

System	Reyco 91 Spring Ride c/w 4 Leaf Spring Optional: Hendrickson Intraax AANT 23K LDA 14" Air Ride
Wheel Seals	Stemco Guardian
Brakes	16 1/2" X 7" Extended Life
Antilock Braking System	Meritor Wabco 2S1M (2 Sensors / 1 Modulator) Optional: 2S2M (2 Sensors / 2 Modulators)
Axle Spread	49" Tandem, 77 1/2" Track Width
Auto Slack Adjusters	Gunite
Spring Brake Pots	Service Brake Pots
Wheel End	Cast Hub and Drum Optional: Duralight Hub and Centrifuse Drum Combinations Optional: Hubodometer - Metric or Imperial

PAINT AND FINISH:

Blast Preparation	Completely Steel Shot Blasted
Special Coatings	Pure Zinc on Complete Outside Top To Bottom
Primer	PPG Epoxy Primer Inside and Out
Top Coat	PPG Urethane / Acrycote Systems - All Colours Available
Professional Cure System	Entire Trailer put in Heat Ovens for Optimal Paint Adhesion
Safety	Reflective Tape

LIGHTING:

Wiring Harness

Severe Duty Sealed Harness System
Custom Designed by Trucklite for our Light Packages

PROTECTIVE FEATURES:

Mudflaps

Doepker Mudflaps at Back
Optional: Mudflaps in Front of Brake Pots on Front Axle

Fenders

1/2 Round Aluminum Fenders

Steps

3 Graded Steps for Access to Front of Dollie
Anti Slip Tape